

*** Patented MAX In-Wall™
Technical Specifications**

MAX In-Wall™ 5RCA



The MAX In-Wall™ 5RCA Module inserts into any MIW-POWER unit to protect against surges on both signal and power lines; thus, eliminating potential grounding problems by creating an Isolated Ground Reference for the remote equipment. The MIW-5RCA accepts RGBHV, component video, and/or stereo audio signal lines running between source components and remote equipment. Devices connect to color-coded RCA connectors on the face of the module. Cabling inside the wall connects to positive-lock BNC connectors. Protect multiple signal lines with one module and the installation flexibility the MIW-5RCA delivers.

GENERAL

Product Name _____ MAX In-Wall™ 5RCA
 Part Number _____ MIW-5RCA
 Retail Price _____ \$59.95
 Application _____ Custom Home Theater Systems
 Power Cord _____ NO
 UL Listed (UL497) _____ YES

SIGNAL LINE PROTECTION

Attenuation _____ <0.6dB, 0-38MHz <1.9dB at 100MHz
 Wires Protected _____ 5 RG179U cables (10 wires)
 Protection Mode _____ Signal/Sheath to Ground
 Clamping _____ 9.0V

PRODUCT WARRANTY

Product Warranty _____ 3 years

ORDERING INFORMATION

Unit Dimensions _____ 1.19"W x 5.50"L x 2.88"H
 Individual Unit UPC _____ 0 50616 00733 7
 Packaging Type _____ Retail Box
 Packaging Dimensions _____ 2.95"W x 1.35"L x 7.85"H
 Unit Weight (packaged) _____ 0.6 lbs.
 Units per Inner Pack _____ 6
 Inner Pack UPC _____ 3 00 50616 00733 8
 Inner Pack Dimensions _____ 6.50"W x 4.80"L x 8.40"H
 Inner Pack Weight _____ 4.0 lbs.
 Units per Master Carton _____ 24 (4 Inner Packs)
 Master Carton UPC _____ 5 00 50616 00733 2
 Master Carton Dimensions _____ 9.90"W x 13.30"D x 8.70"H
 Master Carton Weight _____ 17 lbs.